


PRODUCT PORTFOLIO

Liquid Temperature Control from -95 °C ... +400 °C



Content



Water baths and shaking water baths
PURA, SW

5



Refrigerated and heating circulators
CORIO, DYNEO, MAGIO

06 - 15



Highly dynamic temperature control systems
PRESTO, FORTE HT

16 - 17



Recirculating coolers and chillers
F-, FL-Series

18 - 19

THE RIGHT PRODUCT FOR EVERY APPLICATION



WATER BATHS AND SHAKING WATER BATHS PURA, SW

JULABO offers water baths and shaking water baths for routine applications, such as temperature applications for samples, incubation, material testing, corrosion tests, as well as temperature control applications of cultivations or temperature tests for food and beverages. All models are durable and of high quality. Their working temperature ranges from +18 °C to +99.9 °C qualify them for a wide range of applications.



REFRIGERATED AND HEATING CIRCULATORS CORIO, DYNEO, MAGIO

Refrigerated and heating circulators made by JULABO are used worldwide. Whether in research, material testing or technical systems, users in industries worldwide rely on the tried and tested technology. Focused on your requirements, JULABO circulators have set the benchmark for temperature control technology for decades. The JULABO range of circulators offers the functional solution for your day-to-day work, whether routine tasks or highest requirements: CORIO, DYNEO and MAGIO – three model series for every requirement and every budget.



HIGHLY DYNAMIC TEMPERATURE CONTROL SYSTEMS PRESTO, FORTE HT

Highly dynamic temperature control systems solve even difficult temperature control tasks within no time. With their extremely short heat-up and cool-down times, a wide range of working temperatures without changing the bath fluid, and high output data, they are ideal for compensating temperature differences in external applications extremely quickly. Unlike conventional circulators, the bath fluid can be used in an extended temperature range and for a significantly longer time.





RECIRCULATING COOLERS AND CHILLERS F, FL - Series

JULABO recirculating coolers can handle virtually any cooling requirements in laboratories or industrial environments. Their efficiency makes them an environmentally-friendly and economical alternative to cooling with tap water. Compact models from JULABO are ideal for placement on or underneath a lab bench. JULABO offers several powerful models with up to 20 kW of cooling capacity for applications in industrial environments.



INSTRUMENTS FOR SPECIAL REQUIREMENTS

Calibration baths, forcing test circulators, immersion coolers, flow-through coolers, laboratory temperature controllers, wireless communication & software



With a temperature stability of $\pm 0.005^\circ\text{C}$, calibration baths are suited for the calibration of measuring instruments, thermometers etc. The forcing test circulator specializes in determining the shelf life of beer. Immersion and flow-through coolers are the ideal add-on for quick cool-down of heating circulators and water baths. Temperature controllers are used for measuring, controlling, and monitoring electrically-heated equipment in laboratories.

WATER BATHS AND SHAKING WATER BATHS

PURA | SW




High quality. Practical. Durable.

Users place high demands on modern water baths in terms of functionality and reliability. Above all, a water bath must be trouble-free and low-maintenance in everyday operations. For this reason, JULABO does not only count on proven functions in the new PURA series of water baths, but particularly also on simple, intuitive operation and high material and component quality.

Experienced and safe.

A shaking water bath from JULABO provides the convenience of a water-proof membrane keypad and a bright multi-display (LED) for indication of up to four different values. Microprocessor technology with PID temperature control ensures optimal temperature stability in the water bath.



Product brochure
online at
www.julabo.com

PURA water baths

- Working temperature range¹⁾ from +18 °C to +99.9 °C
- Models with bath volumes from 0.8 to 36 liters
- Heating capacity up to 2 kW
- Splash-proof protected mains switch
- Built-in dry running protection
- Removable platform for full immersion of the sample containers (included)

Shaking water baths

- Working temperature ranges from +20 °C to +99.9 °C
- Dry-running protection with acoustic and optical alarm
- Warning and cut-off protection for high/low temperature
- Adjustable shaking frequency from 20 to 200 rpm
- Drain-screw for emptying
- Removable bottom cover plate and shaking insert

PURA & Shaking Waterbaths – technical data

| Model | Order No.. | Working temperature range ¹⁾ °C | Temperature stability ²⁾ °C | Heating capacity kW | Possible test tube racks (accessories) | Bath opening/bath depth W×L / D cm | Filling volume liters | Dimensions without cover W×D×H cm |
|---------|------------|---|---|------------------------|---|---------------------------------------|--------------------------|--------------------------------------|
| PURA 4 | 9 550 504 | +18 ... +99.9 | ±0.15 | 0.5 | 1 | 12 × 27 / 14 | 0.8 ... 4.5 | 21 × 38 × 30 |
| PURA 10 | 9 550 510 | +18 ... +99.9 | ±0.15 | 1.2 | 2 | 22 × 27 / 14 | 1.4 ... 9.5 | 31 × 38 × 30 |
| PURA 14 | 9 550 514 | +18 ... +99.9 | ±0.15 | 1.8 | 3 | 33 × 27 / 17 | 2 ... 14 | 42 × 38 × 30 |
| PURA 22 | 9 550 522 | +18 ... +99.9 | ±0.15 | 2 | 5 | 55 × 27 / 18 | 3.4 ... 25.5 | 63 × 38 × 30 |
| PURA 30 | 9 550 530 | +18 ... +99.9 | ±0.15 | 2 | 7 | 77 × 27 / 18 | 4.8 ... 36 | 85 × 38 × 30 |

| Model | Order No.. | Working temperature range ¹⁾ °C | Temperature stability ²⁾ °C | Heating capacity kW | Shaking frequency U/min | Shaking stroke mm | Bath opening/bath depth W×L / D cm | Filling volume liters | Dimensions without cover W×D×H cm |
|-------|------------|---|---|------------------------|----------------------------|----------------------|---------------------------------------|--------------------------|--------------------------------------|
| SW22 | 9 550 322 | +20 ... +99.9 | ±0.2 | 2 | 20 ... 200 | 15 | 50 × 30 / 18 | 8 ... 20 | 70 × 35 × 26 |
| SW23 | 9 550 323 | +20 ... +99.9 | ±0.02 | 2 | 20 ... 200 | 15 | 50 × 30 / 18 | 8 ... 20 | 70 × 35 × 26 |

¹⁾ with counter-cooling/bath cover (accessories) ²⁾ with bath cover (accessories)




REFRIGERATED CIRCULATORS

CORIO

The CORIO series is the gateway to professional temperature control, with future-oriented technology that makes high demands on accuracy, economy, and handling. The CORIO program offers different models for daily work and routine tasks in the lab.

Powerful.

- For internal and / or external applications
- Models for working temperatures from -50 °C to +200 °C
- Very quiet operation
- All models feature user-friendly, intuitive operation
- Bright displays, easy to read even from a distance
- State-of-the-art control technology for quick results and precision
- USB interface
- RS232 (CORIO CP)
- Refrigeration units without side vents
- Built-in drain tap for easy and safe drainage
- Optimized cooling coil design provides more space in the bath



Product brochure
online at
www.julabo.com



CORIO™



NATURAL REFRIGERANT

Units with this symbol work with environmentally friendly, natural refrigerants.

Saves energy.

JULABO refrigerated circulators use various energy-efficient components and technologies to minimize both power consumption and waste heat in the laboratory.

Maintenance. Friendly.

The magnetic front grid can be removed easily for user-friendly cleaning and maintenance. No tools are needed.



Accessories at
www.julabo.com

CORIO refrigerated circulators – technical data

The refrigerated circulators of the CORIO series provide a heating capacity of 2 kW as well as a temperature stability of ± 0.03 °C.

| Model | Order No. | Working temperature range °C | Cooling capacity (kW) at bath temperature in °C | | | Pressure bar | Pump Flow rate l/min | Bath opening/bath depth W x L/D cm | Filling volume liters | Dimensions W x D x H cm |
|-----------|--------------|---------------------------------|---|------|------|--------------|----------------------|------------------------------------|-----------------------|-------------------------|
| | | | +20 | 0 | -20 | | | | | |
| CD-200F | 9 012 701 | -20 ... +150 | 0.22 | 0.17 | 0.06 | 0.35 | 15 | 13 x 15 / 15 | 3 ... 4 | 23 x 39 x 65 |
| CP-200F | 9 013 701 | -20 ... +200 | 0.2 | 0.15 | 0.02 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 39 x 65 |
| CD-201F | 9 012 702 | -20 ... +150 | 0.22 | 0.16 | 0.06 | 0.35 | 15 | 13 x 15 / 15 | 3 ... 4 | 44 x 41 x 44 |
| CP-201F | 9 013 702 | -20 ... +200 | 0.2 | 0.15 | 0.02 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 44 x 41 x 44 |
| CD-300F | 9 012 703 | -25 ... +150 | 0.31 | 0.28 | 0.11 | 0.35 | 15 | 13 x 15 / 15 | 3 ... 4 | 24 x 42 x 66 |
| CP-300F | 9 013 703 | -25 ... +200 | 0.3 | 0.27 | 0.08 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 24 x 42 x 66 |
| CD-310F | 9 012 713.N1 | -30 ... +150 | 0.31 | 0.28 | 0.13 | 0.35 | 15 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| CP-310F | 9 013 713.N1 | -30 ... +200 | 0.3 | 0.27 | 0.12 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| CD-450F | 9 012 714.N1 | -30 ... +150 | 0.45 | 0.38 | 0.17 | 0.35 | 15 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| CP-450F | 9 013 714.N1 | -30 ... +200 | 0.44 | 0.37 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| CD-449F | 9 012 716.N1 | -32 ... +150 | 0.45 | 0.36 | 0.21 | 0.35 | 15 | 28 x 35 / 20 | 20 ... 26 | 37 x 59 x 69 |
| CP-449F | 9 013 716.N1 | -32 ... +200 | 0.44 | 0.35 | 0.2 | 0.1 ... 0.7 | 8 ... 27 | 28 x 35 / 20 | 20 ... 26 | 37 x 59 x 69 |
| CD-600F | 9 012 704 | -35 ... +150 | 0.6 | 0.46 | 0.18 | 0.35 | 15 | 22 x 15 / 15 | 5 ... 7.5 | 33 x 47 x 69 |
| CP-600F | 9 013 704 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 22 x 15 / 15 | 5 ... 7.5 | 33 x 47 x 69 |
| CD-601F | 9 012 705 | -35 ... +150 | 0.6 | 0.46 | 0.18 | 0.35 | 15 | 22 x 15 / 20 | 8 ... 10 | 33 x 47 x 74 |
| CP-601F | 9 013 705 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 22 x 15 / 20 | 8 ... 10 | 33 x 47 x 74 |
| CD-800F | 9 012 715 | -40 ... +150 | 0.85 | 0.75 | 0.4 | 0.35 | 15 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| CP-800F | 9 013 715 | -40 ... +200 | 0.84 | 0.74 | 0.39 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| CD-1000F | 9 012 707 | -40 ... +150 | 1 | 0.98 | 0.53 | 0.35 | 15 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| CP-1000F | 9 013 707 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| CD-1000FW | 9 012 727 | -40 ... +150 | 1 | 0.98 | 0.53 | 0.35 | 15 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| CP-1000FW | 9 013 727 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| CD-1001F | 9 012 708 | -38 ... +100 | 1 | 0.9 | 0.35 | 0.35 | 15 | 35 x 41 / 30 | 42 ... 56 | 45 x 64 x 95 |
| CP-1001F | 9 013 708 | -38 ... +100 | 1 | 0.9 | 0.32 | 0.1 ... 0.7 | 8 ... 27 | 35 x 41 / 30 | 42 ... 56 | 45 x 64 x 95 |
| CD-1200F | 9 012 717 | -40 ... +150 | 1.25 | 1.1 | 0.63 | 0.35 | 15 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| CP-1200F | 9 013 717 | -50 ... +200 | 1.24 | 1.09 | 0.62 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| CD-1200FW | 9 012 728 | -40 ... +150 | 1.25 | 1.1 | 0.63 | 0.35 | 15 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| CP-1200FW | 9 013 728 | -50 ... +200 | 1.24 | 1.09 | 0.62 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |



REFRIGERATED CIRCULATORS

DYNEO

The DYNEO circulator range focuses on your needs and offers innovative temperature control technology as well as functional solutions for demanding internal and external temperature applications.



Product brochure
online at
www.julabo.com

Powerful.

- For internal and / or external applications
- Models for working temperatures from -50 °C to +200 °C
- Models suitable for internal and external applications
- Continuously adjustable, powerful pressure pump
- Flow rate 27 l/min, supply pressure 0.7 bar
- Easy switch between internal and external circulation
- Large color TFT display, multi-lingual user interface
- Ease of use via central rotary knob
- Integrated programmer
- External Pt100 sensor connection
- USB interface
- RS232 interface or analog interfaces (optional)
- Built-in drain tap for easy and safe drainage



DYNEO™


**NATURAL
REFRIGERANT**

Units with this symbol work with environmentally friendly, natural refrigerants.

DYNEO. Intelligent, simple control.

The rotary knob of the DYNEO series provides for simple, modern control options. The entire menu, all functions and settings are controlled directly via the central rotary knob on the front of the circulator.


DYNEO refrigerated circulators – technical data

The refrigerated circulators of the DYNEO series provide a heating capacity of 2 kW as well as a temperature stability of $\pm 0.01^\circ\text{C}$.

| Model | Order No. | Working temperature range $^\circ\text{C}$ | Cooling capacity (kW) at bath temperature in $^\circ\text{C}$ | | | Pressure bar | Pump Flow rate l/min | Usable bath opening W x L / D cm | Filling volume liters | Dimensions W x L x H cm |
|-----------|--------------|---|---|------|------|--------------|----------------------|----------------------------------|-----------------------|-------------------------|
| | | | +20 | 0 | -20 | | | | | |
| DD-200F | 9 021 701 | -20 ... +200 | 0.2 | 0.15 | 0.02 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 39 x 65 |
| DD-201F | 9 021 702 | -20 ... +200 | 0.2 | 0.15 | 0.02 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 44 x 41 x 44 |
| DD-300F | 9 021 703 | -25 ... +200 | 0.3 | 0.27 | 0.08 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 24 x 42 x 66 |
| DD-310F | 9 021 713.N1 | -30 ... +200 | 0.3 | 0.27 | 0.12 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| DD-450F | 9 021 714.N1 | -30 ... +200 | 0.44 | 0.37 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 13 x 15 / 15 | 3 ... 4 | 23 x 40 x 65 |
| DD-449F | 9 021 716.N1 | -32 ... +200 | 0.44 | 0.35 | 0.2 | 0.1 ... 0.7 | 8 ... 27 | 28 x 35 / 20 | 20 ... 26 | 37 x 59 x 69 |
| DD-600F | 9 021 704 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 22 x 15 / 15 | 5 ... 7.5 | 33 x 47 x 69 |
| DD-601F | 9 021 705 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.1 ... 0.7 | 8 ... 27 | 22 x 15 / 20 | 8 ... 10 | 33 x 47 x 74 |
| DD-800F | 9 021 715 | -40 ... +200 | 0.84 | 0.74 | 0.39 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| DD-1000F | 9 021 707 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| DD-1000FW | 9 021 727 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 42 x 49 x 74 |
| DD-1001F | 9 021 708 | -38 ... +100 | 1 | 0.85 | 0.32 | 0.1 ... 0.7 | 8 ... 27 | 35 x 41 / 30 | 42 ... 56 | 45 x 64 x 95 |
| DD-1200F | 9 021 717 | -50 ... +200 | 1.24 | 1.09 | 0.62 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |
| DD-1200FW | 9 021 728 | -50 ... +200 | 1.24 | 1.09 | 0.62 | 0.1 ... 0.7 | 8 ... 27 | 18 x 13 / 15 | 5 ... 7.5 | 33 x 47 x 70 |

Optional extension of interfaces

Upon customer request, all DYNEO circulators can be equipped with an additional digital or analog interface for integration into process systems. To do this, simply add an ".A" for the analog interface or a ".D" for the digital interface to the end of the order number.





REFRIGERATED CIRCULATORS

MAGIO

From research institutes to industrial companies, laboratories around the world need high performance circulators for challenging temperature applications.

The high-end circulators in the MAGIO range have been specially developed by JULABO with pioneering technologies for these requirements and are manufactured to the highest quality standards in Germany.



Product brochure
online at
www.julabo.com

Powerful.

- Ideal for demanding external applications
- Simple control of complex applications
- Continuously adjustable, extremely powerful pressure/suction pump
- Flow rate 16 ... 31 l/min, supply pressure 0.24 ... 0.92 bar, suction 0.03 ... 0.4 bar
- Large, high-resolution TFT touch display with multilingual user interface
- Stainless steel parts in contact with the medium
- Integrated programmer
- External Pt100 sensor connection
- USB interface
- RS232 interface
- Ethernet interface
- Analog interfaces (accessories)
- Classification III according to DIN 12876-1



MAGIO™


**NATURAL
REFRIGERANT**

Units with this symbol work with environmentally friendly, natural refrigerants.


MAGIO refrigerated circulators – technical data

All refrigerated circulators have a temperature stability of $\pm 0,01$ °C and a heating capacity of 2 kW (MAGIO MS) or 3 kW (MAGIO MX).

| Model | Order No. | Working temperature range °C | Cooling capacity (kW) at bath temperature in °C | | | Pump | | | Usable bath opening W×L/D | Filling volume liters | Dimensions W×L×H cm |
|------------------|---------------------|---------------------------------|--|------|------|---------------|--------------|-----------------|---------------------------|--------------------------|------------------------|
| | | | +20 | 0 | -20 | Pressure bar | Suction bar | Flow rate l/min | | | |
| MS-310F | 9 032 713.N1 | -30 ... +200 | 0.26 | 0.21 | 0.10 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 13×15/15 | 3 ... 4 | 23×40×65 |
| MS-450F | 9 032 714.N1 | -30 ... +200 | 0.4 | 0.33 | 0.12 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 13×15/15 | 3 ... 4 | 23×40×65 |
| MS-449F | 9 032 716.N1 | -30 ... +200 | 0.4 | 0.31 | 0.19 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 28×35/20 | 18 ... 26 | 37×59×69 |
| MS-600F | 9 032 704 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 22×15/15 | 5 ... 7.5 | 33×47×69 |
| MS-601F | 9 032 705 | -35 ... +200 | 0.6 | 0.44 | 0.16 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 22×15/20 | 8 ... 10 | 33×47×74 |
| MS-800F | 9 032 715 | -40 ... +200 | 0.86 | 0.76 | 0.41 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/15 | 5 ... 7.5 | 33×47×70 |
| MS-1000F | 9 032 707 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/15 | 5 ... 7.5 | 42×49×74 |
| MS-1000FW | 9 032 727 | -50 ... +200 | 1 | 0.96 | 0.51 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/15 | 5 ... 7.5 | 42×49×74 |
| MS-1200F | 9 032 717 | -50 ... +200 | 1.26 | 1.11 | 0.64 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/15 | 5 ... 7.5 | 33×47×70 |
| MS-1200FW | 9 032 728 | -50 ... +200 | 1.24 | 1.09 | 0.62 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/15 | 5 ... 7.5 | 33×47×70 |
| MX-1800F | 9 033 751 | -50 ... +200 | 1.8 | 1.5 | 0.7 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/20 | 6.5 ... 11 | 40×50×86 |
| MX-2500F | 9 033 752 | -50 ... +200 | 2.5 | 1.8 | 0.85 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 18×13/20 | 6.5 ... 11 | 40×50×86 |

High-resolution TFT touch display

The modern TFT touch display gives you all important information at a glance. Three large, predefined main screens clearly display data and graphics with various application priorities. Menu navigation is self-explanatory, arranged by relevance to daily operations and easy to operate with the touch of a finger. The Help function provides detailed support in case of additional questions.





HEATING CIRCULATORS

CORIO | DYNEO | MAGIO

Heating technology from +20 °C to +300 °C.

Heating circulators made by JULABO are used worldwide. Whether in research, material testing or technical systems, users in industries around the world rely on the tried and tested technology. Focused on your requirements, JULABO heating circulators have set the benchmark for temperature control technology for decades. The JULABO range of circulators offers the functional solution for your day-to-day work, whether routine tasks or highest requirements: CORIO, DYNEO and MAGIO – three model series for every requirement and every budget.

Powerful.

- Models for working temperatures from +20 °C to +300 °C
- Available as heating immersion circulators, bridge mounted circulators, open heating bath circulators, bath or heating circulators
- Suitable for internal and/or external applications
- Bath tanks made of transparent plastic or stainless steel (according to choice)





JULABO heating circulators for every application

Heating immersion circulators form the basis of the JULABO circulator portfolio. They can be mounted on bath tanks with up to 50 liters.

The **bridge mounted circulator** is delivered with an adjustable stainless steel telescope bridge.

Open heating bath circulators are suited for internal applications, such as temperature control of samples.

Heating immersion, bridge-mounted and open heating bath circulators – technical data

| Model | Order No. | Working temperature range | Temperature stability | Heating capacity | Pressure | Pump Suction | Flow rate | Usable bath opening W×L/D | Filling volume | Dimensions W×L×H |
|--|-----------|---------------------------|-----------------------|------------------|---------------|--------------|-----------|---------------------------|----------------|------------------|
| Heating immersion circulators CORIO | | | | | | | | | | |
| C | 9 011 000 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | - | - | 13.2 × 16 × 36.2 |
| CD | 9 012 000 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | - | - | 13.2 × 16 × 36.2 |
| CP | 9 013 000 | +20 ... +200 | ± 0.02 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | - | - | 13.2 × 16 × 36.2 |
| Heating immersion circulator DYNEO | | | | | | | | | | |
| DD | 9 021 000 | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | - | - | 13.2 × 16 × 35.5 |
| Bridge mounted circulators MAGIO | | | | | | | | | | |
| MS-Z | 9 032 201 | +20 ... +300 | ± 0.01 | 2 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | - | - | 34 × 19 × 36 |
| MX-Z | 9 033 201 | +20 ... +300 | ± 0.01 | 3 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | - | - | 34 × 19 × 41 |
| Open heating bath circulators CORIO | | | | | | | | | | |
| C-BT5 | 9 011 305 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 15 × 15 / 15 | 3.5 ... 5 | 23 × 38 × 38 |
| C-BT9 | 9 011 309 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 23 × 15 / 15 | 6 ... 9 | 32 × 38 × 38 |
| C-BT19 | 9 011 319 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 35 / 15 | 14 ... 19 | 38 × 58 × 38 |
| C-BT27 | 9 011 327 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 35 / 15 | 20 ... 27 | 38 × 58 × 43 |
| C-B5 | 9 011 405 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 15 × 15 / 15 | 3.5 ... 5 | 23 × 38 × 41 |
| C-B13 | 9 011 413 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 18 / 15 | 9 ... 13 | 38 × 40 × 42 |
| C-B17 | 9 011 417 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 18 / 20 | 13 ... 17 | 38 × 40 × 47 |
| C-B19 | 9 011 419 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 35 / 15 | 14 ... 19 | 38 × 58 × 42 |
| C-B27 | 9 011 427 | +20 ... +100 | ± 0.03 | 2 | 0.1 | - | 6 | 30 × 35 / 20 | 17 ... 27 | 38 × 58 × 47 |

Accessories at
www.julabo.com



HEATING CIRCULATORS

CORIO | DYNEO | MAGIO



Product brochure
online at
www.julabo.com

Heating circulators with open baths for different applications

Heating circulators with open baths can be used for internal and external applications, because the changeover between internal and external temperature control is very easy.

Heating circulators are tailored to external temperature control applications and offer the best heat insulation.

Powerful.

- Models for working temperatures from +20 °C to +300 °C
- Large selection of models for internal and external applications
- Bath tanks made of transparent plastic or stainless steel (according to choice)
- Easy operation
- Bright displays, easy to read even from a distance
- State-of-the-art control technology for quick results and precision
- With many professional functions (model specific) for adjusting control parameters, temperature calibration, temperature profiles, etc.
- Powerful circulating pumps – electronically adjustable
- High heating capacities for rapid heat-up

Accessories at
www.julabo.com



Heating circulators with open baths – technical data

| Model | Order No. | Working temperature range | Tempera-ture stability | Heating capacity | Pressure | Pump Suction | Flow rate | Usable bath opening W×L/D | Filling volume | Dimensions W×L×H |
|-------|-----------|---------------------------|------------------------|------------------|----------|--------------|-----------|---------------------------|----------------|------------------|
| | | °C | °C | kW | bar | bar | l/min | cm | liters | cm |

Heating circulators with open baths CORIO

| | | | | | | | | | | |
|---------|-----------|--------------|--------|---|------|---|----|----------|-----------|----------|
| CD-BT5 | 9 012 305 | +20 ... +100 | ± 0.03 | 2 | 0.35 | - | 15 | 15×15/15 | 3.5 ... 5 | 23×38×38 |
| CD-BT19 | 9 012 319 | +20 ... +100 | ± 0.03 | 2 | 0.35 | - | 15 | 30×35/15 | 14 ... 19 | 38×58×38 |
| CD-BT27 | 9 012 327 | +20 ... +100 | ± 0.03 | 2 | 0.35 | - | 15 | 30×35/20 | 20 ... 27 | 38×58×43 |
| CD-B5 | 9 012 405 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 15×15/15 | 3.5 ... 5 | 23×38×41 |
| CD-B13 | 9 012 413 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 30×18/15 | 9 ... 13 | 38×40×42 |
| CD-B17 | 9 012 417 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 30×18/20 | 13 ... 17 | 38×40×47 |
| CD-B19 | 9 012 419 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 30×35/15 | 14 ... 19 | 38×58×42 |
| CD-B27 | 9 012 427 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 30×35/20 | 17 ... 27 | 38×58×47 |
| CD-B33 | 9 012 433 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 66×32/15 | 26 ... 39 | 91×36×43 |
| CD-B39 | 9 012 439 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 33×30/30 | 35 ... 41 | 54×34×57 |

Heating circulators CORIO

| | | | | | | | | | | |
|---------|-----------|--------------|--------|---|-------------|---|----------|----------|------------|----------|
| CD-BC4 | 9 012 504 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| CP-BC4 | 9 013 504 | +20 ... +200 | ± 0.02 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| CD-BC6 | 9 012 506 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| CP-BC6 | 9 013 506 | +20 ... +200 | ± 0.02 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| CD-BC12 | 9 012 512 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| CP-BC12 | 9 013 512 | +20 ... +200 | ± 0.02 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| CD-BC26 | 9 012 526 | +20 ... +150 | ± 0.03 | 2 | 0.35 | - | 15 | 26×35/20 | 19 ... 26 | 39×62×48 |
| CP-BC26 | 9 013 526 | +20 ... +200 | ± 0.02 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 26×35/20 | 19 ... 26 | 39×62×48 |

Heating circulators DYNEO

| | | | | | | | | | | |
|---------|-------------|--------------|--------|---|-------------|---|----------|----------|------------|----------|
| DD-BC4 | 9 021 504 | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| DD-BC4 | 9 021 504.D | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| DD-BC4 | 9 021 504.A | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| DD-BC6 | 9 021 506 | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| DD-BC6 | 9 021 506.D | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| DD-BC6 | 9 021 506.A | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| DD-BC12 | 9 021 512 | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| DD-BC12 | 9 021 512.D | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| DD-BC12 | 9 021 512.A | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| DD-BC26 | 9 021 526 | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 26×35/20 | 19 ... 26 | 39×62×48 |
| DD-BC26 | 9 021 526.D | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 26×35/20 | 19 ... 26 | 39×62×48 |
| DD-BC26 | 9 021 526.A | +20 ... +200 | ± 0.01 | 2 | 0.1 ... 0.7 | - | 8 ... 27 | 26×35/20 | 19 ... 26 | 39×62×48 |

Heating circulators MAGIO

| | | | | | | | | | | |
|---------|-----------|--------------|--------|---|---------------|--------------|-----------|----------|------------|----------|
| MS-BC4 | 9 032 504 | +20 ... +300 | ± 0.01 | 2 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 13×15/15 | 3 ... 4.5 | 23×41×42 |
| MX-BC6 | 9 033 506 | +20 ... +300 | ± 0.01 | 3 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 13×15/20 | 4.5 ... 6 | 24×44×47 |
| MX-BC12 | 9 033 512 | +20 ... +300 | ± 0.01 | 3 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 22×15/20 | 8.5 ... 12 | 33×49×47 |
| MX-BC26 | 9 033 526 | +20 ... +300 | ± 0.01 | 3 | 0.24 ... 0.92 | 0.03 ... 0.4 | 16 ... 31 | 26×35/20 | 19 ... 26 | 39×62×48 |



HIGHLY DYNAMIC TEMPERATURE CONTROL SYSTEMS

PRESTO | FORTE HT



NATURAL REFRIGERANT

Units with this symbol work with environmentally friendly, natural refrigerants.



Product brochure online at
www.julabo.com

PRESTO: Best performance for highly dynamic temperature control systems

With high cooling and heating capacities, PRESTO systems cover a working temperature range of -93 °C to +250 °C. Their highly efficient components can compensate exothermic and endothermic reactions extremely fast.

- Ideal for high precision, external temperature control tasks from -93 °C ... +250 °C
- Broad working temperature ranges without changing the bath fluid
- Extremely rapid cool-down and heat-up
- Powerful circulation pumps, adjusted in increments or to predefined pressure values

FORTE HT with optional cooling unit

The high temperature circulators of the FORTE HT series control the temperature of external closed systems. These compact instruments have a closed design. Even at high temperatures, there is no offgassing of oil odors.

- High heating capacity up to 7 kW for short heat-up times
- High pump capacity
- Low filling volume
- Cooling water connection for cold oil overlay
- External Pt100 sensor connection
- Numerous interfaces

Accessories at
www.julabo.com

FORTE HT without cooling unit



FORTE HT with cooling unit



Models with C.U. cooling units also provide:

- Pulsed cooling water supply for temperature control tasks starting at +40 °C
- Cooling power up to max. 15 kW (cooling water at +20 °C and oil temperature at +300 °C)
- Rapid cool-down to low temperatures in very little time
- Fast compensation, e.g. of exothermal reactions

PRESTO™




Highly dynamic temperature control systems – technical data

| Model | Order No. | Working temperature range °C | Temperature stability °C | Heating capacity kW | Cooling capacity (kW) at bath temperature in °C | | | Pump Pressure bar | Flow rate l/min | Cooling of refrigerant unit | Dimensions W × D × H cm |
|---|--------------|---------------------------------|-----------------------------|------------------------|--|------|------|----------------------|--------------------|-----------------------------|----------------------------|
| PRESTO | | | | | | | | | | | |
| A30 | 9 420 300 | -30 ... +250 | ±0.01 ... ±0.05 | 2.7 | 0.5 | 0.4 | 0.2 | 0.5 | 25 | 1-st. Air | 25 × 59 × 62 |
|  A38 | 9 420 381.N1 | -45 ... +250 | ±0.01 ... ±0.05 | 2.7 | 0.79 | 0.73 | 0.44 | 0.1 ... 1.6 | 0 ... 50 | 1-st. Air | 33 × 75 × 67 |
| A40 | 9 420 401 | -40 ... +250 | ±0.01 ... ±0.05 | 2.7 | 1.2 | 0.9 | 0.6 | 0.1 ... 1.7 | 0 ... 40 | 1-st. Air | 33 × 59 × 67 |
|  W40 | 9 421 401 | -40 ... +250 | ±0.01 ... ±0.05 | 2.7 | 1.2 | 1. | 0.55 | 0.1 ... 1.7 | 0 ... 40 | 1-st. Water | 33 × 59 × 67 |
|  A41 | 9 420 411.N1 | -45 ... +250 | ±0.01 ... ±0.05 | 2.7 | 1.33 | 1.24 | 0.46 | 0.1 ... 1.6 | 0 ... 50 | 1-st. Air | 33 × 75 × 67 |
|  W41 | 9 421 411.N1 | -45 ... +250 | ±0.01 ... ±0.05 | 2.7 | 1.33 | 1.24 | 0.46 | 0.1 ... 1.6 | 0 ... 50 | 1-st. Water | 33 × 75 × 67 |
| A45 | 9 420 452 | -45 ... +250 | ±0.05 ... ±0.1 | 6 | 3.5 | 3.3 | 1.8 | 0.1 ... 3 | 0 ... 80 | 1-st. Air | 53 × 66.5 × 126 |
| A45t | 9 420 452.T | -45 ... +250 | ±0.05 ... ±0.1 | 12 | 3.5 | 3.3 | 1.8 | 0.1 ... 3 | 0 ... 80 | 1-st. Air | 53 × 66.5 × 126 |
| W50 | 9 421 502 | -50 ... +250 | ±0.05 ... ±0.1 | 6 | 7.5 | 6.5 | 3 | 0.1 ... 3 | 0 ... 80 | 1-st. Water | 53 × 66.5 × 126 |
| W50t | 9 421 502.T | -50 ... +250 | ±0.05 ... ±0.1 | 12 | 7.5 | 6.5 | 3 | 0.1 ... 3 | 0 ... 80 | 1-st. Water | 53 × 66.5 × 126 |
| W55 | 9 421 552 | -55 ... +250 | ±0.05 ... ±0.2 | 15 | 15 | 10 | 4 | 0.1 ... 3 | 0 ... 80 | 1-st. Water | 61 × 84.5 × 125 |
| W56 | 9 421 562 | -56 ... +250 | ±0.05 ... ±0.1 | 27 | 25.8 | 23.1 | 11.5 | 0.1 ... 3 | 0 ... 80 | 1-st. Water | 60 × 94 × 164 |
| W56x | 9 421 563.S1 | -50 ... +250 | ±0.05 ... ±0.1 | 27 | 25.8 | 23.1 | 11.5 | 0.1 ... 5.5 | 0 ... 70 | 1-st. Water | 60 × 94 × 164 |
| W58x | 9 421 583.S1 | -50 ... +250 | ±0.05 ... ±0.1 | 27 | 33 | 32 | 19 | 0.1 ... 5.5 | 0 ... 70 | 1-st. Water | 70 × 108 × 174 |
|  A70 | 9 420 701.N1 | -75 ... +250 | ±0.01 ... ±0.05 | 1.8 | 1 | 0.91 | 0.84 | 0.1 ... 1.7 | 0 ... 40 | 2-st. Air | 57 × 74.5 × 88 |
| A80 | 9 420 801 | -80 ... +250 | ±0.01 ... ±0.05 | 1.8 | 1.2 | 1.2 | 1.1 | 0.1 ... 1.7 | 0 ... 40 | 2-st. Air | 43 × 65 × 126 |
| A80t | 9 420 801.T | -80 ... +250 | ±0.01 ... ±0.05 | 3.4 | 1.2 | 1.2 | 1.1 | 0.1 ... 1.7 | 0 ... 40 | 2-st. Air | 43 × 65 × 126 |
| W80 | 9 421 801 | -80 ... +250 | ±0.01 ... ±0.05 | 1.8 | 1.2 | 1.2 | 1.1 | 0.1 ... 1.7 | 0 ... 40 | 2-st. Water | 43 × 65 × 126 |
| W80t | 9 421 801.T | -80 ... +250 | ±0.01 ... ±0.05 | 3.4 | 1.2 | 1.2 | 1.1 | 0.1 ... 1.7 | 0 ... 40 | 2-st. Water | 43 × 65 × 126 |
| A85 | 9 420 852 | -85 ... +250 | ±0.05 ... ±0.1 | 6 | 2.5 | 2.4 | 2.4 | 0.1 ... 3 | 0 ... 80 | 2-st. Air | 61 × 108 × 125 |
| A85t | 9 420 852.T | -85 ... +250 | ±0.05 ... ±0.1 | 15 | 2.5 | 2.4 | 2.4 | 0.1 ... 3 | 0 ... 80 | 2-st. Air | 61 × 108 × 125 |
| W85 | 9 421 852 | -85 ... +250 | ±0.05 ... ±0.1 | 6 | 2.5 | 2.4 | 2.4 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 61 × 84.5 × 125 |
| W85t | 9 421 852.T | -85 ... +250 | ±0.05 ... ±0.1 | 15 | 2.5 | 2.4 | 2.4 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 61 × 84.5 × 125 |
| W91 | 9 421 912 | -91 ... +250 | ±0.05 ... ±0.2 | 18 | 11 | 11 | 11 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 95 × 127 × 190 |
| W91tt | 9 421 912.TT | -91 ... +250 | ±0.05 ... ±0.2 | 36 | 11 | 11 | 11 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 95 × 127 × 190 |
| W91x | 9 421 913 | -91 ... +250 | ±0.05 ... ±0.2 | 18 | 11 | 11 | 11 | 0.1 ... 5.5 | 0 ... 70 | 2-st. Water | 95 × 127 × 190 |
| W91tx | 9 421 913.TT | -91 ... +250 | ±0.05 ... ±0.2 | 36 | 11 | 11 | 11 | 0.1 ... 5.5 | 0 ... 70 | 2-st. Water | 95 × 127 × 190 |
| W92 | 9 421 922 | -92 ... +250 | ±0.05 ... ±0.2 | 18 | 27 | 20 | 11 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 95 × 127 × 190 |
| W92tt | 9 421 922.TT | -92 ... +250 | ±0.05 ... ±0.2 | 36 | 27 | 20 | 11 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 95 × 127 × 190 |
| W92x | 9 421 923 | -92 ... +250 | ±0.05 ... ±0.2 | 18 | 27 | 20 | 11 | 0.1 ... 5.5 | 0 ... 70 | 2-st. Water | 95 × 127 × 190 |
| W92tx | 9 421 923.TT | -92 ... +250 | ±0.05 ... ±0.2 | 36 | 27 | 20 | 11 | 0.1 ... 5.5 | 0 ... 70 | 2-st. Water | 95 × 127 × 190 |
|  W93 | 9 421 932.N1 | -93 ... +250 | ±0.05 ... ±0.2 | 27 | 19.5 | 19.5 | 19.5 | 0.1 ... 3 | 0 ... 80 | 2-st. Water | 93 × 148 × 192 |
|  W93x | 9 421 933.N1 | -93 ... +250 | ±0.05 ... ±0.2 | 27 | 19.5 | 19.5 | 19.5 | 0.1 ... 5.5 | 0 ... 70 | 2-st. Water | 93 × 148 × 192 |

| Model | Order No. | Working temperature range °C | Temperature stability external °C | Heating capacity kW | Cooling capacity (water +20 °C) kW, max. | Pump Pressure bar | Flow rate l/min | Dimensions Circulator W × D × H cm | Dimensions Control electronics W × D × H cm |
|-----------------|-----------|---------------------------------|--------------------------------------|------------------------|---|----------------------|--------------------|---------------------------------------|--|
| FORTE HT | | | | | | | | | |
| HT30-M1 | 9 800 031 | +70 ... +400 | ±0.01 ... ±0.1 | 3 | - | 0.8 - 1.2 | 14 - 18 | 23 × 23 × 58 | 25 × 25 × 18 |
| HT60-M2 | 9 800 062 | +70 ... +400 | ±0.01 ... ±0.1 | 7 | - | 0.8 - 1.2 | 14 - 18 | 23 × 23 × 58 | 25 × 25 × 18 |
| HT60-M3 | 9 800 063 | +70 ... +400 | ±0.01 ... ±0.1 | 6 | - | 0.8 - 1.2 | 14 - 18 | 23 × 23 × 58 | 25 × 25 × 18 |
| HT30-M1-C.U. | 9 800 035 | +40 ... +400 | ±0.01 ... ±0.1 | 3 | 15 | 0.8 - 1.2 | 14 - 18 | 43 × 23 × 58 | 25 × 25 × 18 |
| HT60-M2-C.U. | 9 800 065 | +40 ... +400 | ±0.01 ... ±0.1 | 7 | 15 | 0.8 - 1.2 | 14 - 18 | 43 × 23 × 58 | 25 × 25 × 18 |
| HT60-M3-C.U. | 9 800 066 | +40 ... +400 | ±0.01 ... ±0.1 | 6 | 15 | 0.8 - 1.2 | 14 - 18 | 43 × 23 × 58 | 25 × 25 × 18 |



RECIRCULATING COOLERS AND CHILLERS

AWC | F | FL-Series



Product brochure
online at
www.julabo.com



AC100 for working near
ambient temperature

Environmentally-friendly cooling while saving tap water.

JULABO recirculating coolers and chillers are powerful solutions for a wide range of cooling requirements in laboratories and industrial environments. The instruments' short cool-down times and high efficiency make them an economic alternative to tap water cooling. The compact design offers a space saving installation. The instruments are equipped with a bright LED temperature display, easy to read even from a distance. W models are water-cooled for quiet operation and low heat waste. Warning and safety functions enable reliable, continuous operation. Filling and emptying is quick and easy via a well accessible filling and/or drain tap.

Air-to-water recirculating cooler AWC100

- Particularly small space requirement
- Energy-saving
- Cooling capacity adjustable in two steps

F models: compact recirculating coolers

- Working temperature ranges from -10 °C to +40 °C
- Cooling capacity up to 1 kW
- Environmentally-friendly operation with low energy consumption

FL models: powerful recirculating coolers

- Working temperature ranges from -25 °C to +40 °C
- Cooling capacity up to 20 kW
- Powerful circulating pumps



Drain tap located behind
removable venting grid



Accessories at
www.julabo.com



Recirculating coolers and chillers – technical data

| Model | Order No. | Working temperature range | Temperature stability | Cooling capacity (kW) at bath temperature in °C | | | Pump Pressure bar | Flow rate l/min | Cooling of refrigerant unit | Filling volume liters | Dimensions W×D×H cm |
|-------|-----------|---------------------------|-----------------------|---|---|-----|-------------------|-----------------|-----------------------------|-----------------------|---------------------|
| | | °C | °C | +20 | 0 | -20 | | | | | |

Air-to-water recirculating cooler

| | | | | | | | | | | | |
|----------------------|-----------|-------------|--|------|---|---|-----|-----|-----|-----|----------|
| AWC100 ¹⁾ | 9 630 100 | +20 ... +40 | | 0.55 | - | - | 0.2 | 2.9 | Air | 0.9 | 20×34×30 |
|----------------------|-----------|-------------|--|------|---|---|-----|-----|-----|-----|----------|

Compact recirculating coolers, F series

| | | | | | | | | | | | |
|-------|-----------|-------------|------|------|------|---|------|----|-----|-------------|------------|
| F250 | 9 620 025 | -10 ... +40 | ±0.5 | 0.25 | 0.18 | - | 0.35 | 15 | Air | 1.7 ... 2.6 | 24×40×52 |
| F500 | 9 620 050 | 0 ... +40 | ±0.5 | 0.5 | 0.25 | - | 0.5 | 24 | Air | 5 ... 7.5 | 37.5×44×59 |
| F1000 | 9 620 100 | 0 ... +40 | ±0.5 | 1 | 0.35 | - | 1 | 23 | Air | 7 ... 9.5 | 37.5×49×64 |

Recirculating coolers, FL series

| | | | | | | | | | | | |
|----------|-----------|-------------|------|------|-----|------|-----------|----|-------|-----------|------------|
| FL300 | 9 660 003 | -20 ... +40 | ±0.5 | 0.3 | 0.2 | 0.1 | 0.35 | 15 | Air | 3 ... 4.5 | 25×50×60 |
| FL601 | 9 661 006 | -20 ... +40 | ±0.5 | 0.6 | 0.4 | 0.2 | 1 | 23 | Air | 5.5 ... 8 | 32×50×60 |
| FL1201 | 9 661 012 | -20 ... +40 | ±0.5 | 1.2 | 0.9 | 0.3 | 1 | 23 | Air | 12 ... 17 | 50×76×64 |
| FL1203 | 9 663 012 | -20 ... +40 | ±0.5 | 1.2 | 0.8 | 0.2 | 0.5 ... 3 | 40 | Air | 12 ... 17 | 50×76×64 |
| FL1701 | 9 661 017 | -20 ... +40 | ±0.5 | 1.7 | 1.1 | 0.4 | 1 | 23 | Air | 12 ... 17 | 50×76×64 |
| FL1703 | 9 663 017 | -20 ... +40 | ±0.5 | 1.7 | 1 | 0.3 | 0.5 ... 3 | 40 | Air | 12 ... 17 | 50×76×64 |
| FLW1701 | 9 671 017 | -20 ... +40 | ±0.5 | 1.7 | 1.1 | 0.4 | 1 | 23 | Water | 12 ... 17 | 50×76×64 |
| FLW1703 | 9 673 017 | -20 ... +40 | ±0.5 | 1.7 | 1 | 0.3 | 0.5 ... 3 | 40 | Water | 12 ... 17 | 50×76×64 |
| FL2503 | 9 663 025 | -20 ... +40 | ±0.5 | 2.5 | 1.5 | 0.55 | 0.5 ... 3 | 40 | Air | 24 ... 30 | 60×76×115 |
| FL2506 | 9 666 025 | -15 ... +40 | ±0.5 | 2.5 | 1 | - | 0.5 ... 6 | 60 | Air | 24 ... 30 | 60×76×115 |
| FL4003 | 9 663 040 | -20 ... +40 | ±0.5 | 4 | 2.4 | 0.65 | 0.5 ... 3 | 40 | Air | 24 ... 30 | 60×76×115 |
| FL4006 | 9 666 040 | -20 ... +40 | ±0.5 | 4 | 1.9 | 0.05 | 0.5 ... 6 | 60 | Air | 24 ... 30 | 60×76×115 |
| FLW2503 | 9 673 025 | -20 ... +40 | ±0.5 | 2.7 | 1.7 | 0.4 | 0.5 ... 3 | 40 | Water | 24 ... 30 | 60×76×115 |
| FLW2506 | 9 676 025 | -15 ... +40 | ±0.5 | 2.5 | 1 | - | 0.5 ... 6 | 60 | Water | 24 ... 30 | 60×76×115 |
| FLW4003 | 9 673 040 | -20 ... +40 | ±0.5 | 4.3 | 2.2 | 0.45 | 0.5 ... 3 | 40 | Water | 24 ... 30 | 60×76×115 |
| FLW4006 | 9 676 040 | -15 ... +40 | ±0.5 | 4 | 1.7 | - | 0.5 ... 6 | 60 | Water | 24 ... 30 | 60×76×115 |
| FL7006 | 9 666 070 | -20 ... +40 | ±0.5 | 7 | 5.1 | 1.55 | 0.5 ... 6 | 60 | Air | 39 ... 47 | 78×85×148 |
| FL11006 | 9 666 110 | -20 ... +40 | ±0.5 | 11 | 7.5 | 3 | 0.5 ... 6 | 60 | Air | 39 ... 47 | 78×85×148 |
| FL20006 | 9 666 200 | -25 ... +40 | ±0.5 | 20 | 10 | 2.5 | 0.8 ... 6 | 80 | Air | 15 ... 37 | 95×115×161 |
| FLW7006 | 9 676 070 | -20 ... +40 | ±0.5 | 7.4 | 7 | 1.3 | 0.5 ... 6 | 60 | Water | 39 ... 47 | 78×85×148 |
| FLW11006 | 9 676 110 | -20 ... +40 | ±0.5 | 11.5 | 7.3 | 2.7 | 0.5 ... 6 | 60 | Water | 39 ... 47 | 78×85×148 |
| FLW20006 | 9 676 200 | -25 ... +40 | ±0.5 | 20 | 12 | 3 | 0.8 ... 6 | 80 | Water | 15 ... 37 | 95×115×161 |

¹⁾ Cooling capacity depends on the temperature difference between return flow and ambient environment.



Scientific Research Instruments Company Private Limited
42-43, 2nd & 3rd Floor, 1st Cross, Gubbalala, Bengaluru - 560 061
Telephone : 080 4757 2577 | 080 4302 5791

Sales

info@srico-labworld.com
Mobile : +91 9900674407

Service

service@srico-labworld.com
Mobile : +91 9900055879

Bhubaneswar | Hyderabad | New Delhi | Navi Mumbai | Vadodara

Ahmedabad | Chandigarh | Chennai | Goa | Guwahati | Kolkata | Lucknow | Pune | Thiruvananthapuram | Visakhapatnam