

**Promotion - 2024**



**Contact us for quotation @ 99006 74407**

# TABLE OF CONTENTS

**SRICO**  
INNOVATIVE LABORATORY TECHNOLOGY

1



10

**Julabo**  
THE TEMPERATURE CONTROL COMPANY

3



10



6



11



6



14

**VACUUBRAND®**

7



14



7



15

**WIGGENS**  
THE MAGIC MOTION

8



15

**Julabo**  
THE TEMPERATURE CONTROL COMPANY

## Refrigerated/Heating Circulators



From Temperature Range  
**-50°C to +200°C**

Contact us @ : +91 99006 74407 | [info@srico-labworld.com](mailto:info@srico-labworld.com)

## About Us:

SRICO is a professionally managed Laboratory / Process Equipment Company established to deliver the best solutions available from internationally reputed manufacturers in the field of Research and Development, Quality Control and Production for industries and institutions.

SRICO is committed to provide the best customer support across India in the areas of Product & application, Consultation, system integration, installation, maintenance, technical service and IQ/OQ documentation.

SRICO's primary focus is to address the laboratory / process equipment-related needs of companies, institutions and universities (from both Government and Private sectors) which are active in the fields of Chemical, Petrochemical, Pharmaceuticals, Biotechnology & Life Sciences, Agricultural & Veterinary Sciences & Food and Environmental Sciences, Automotive, E-mobility, Electronics & semiconductor Industries.

SRICO's product range includes Analytical Instruments, General Laboratory equipment, process temperature control solutions and consumables. The products represented by us are supplied/supported across India through our own branch offices and residential representatives spread across PAN India. In addition, a reliable, reputed and efficient distribution network is available at your door-step to serve your needs all the time.

SRICO's team of Product & Application specialists and Technical Support Engineers will co-ordinate through our colleagues/ Partners across India to provide you the best Product, Application and technical support.

SRICO's team along with its Distribution partners and Principal companies will work as ONE TEAM to provide the most effective and efficient support to end-users and offer the best timely solutions in product, application, and technical service support at an optimal price intended to benefit our customers.

Our mission is to deliver total customer satisfaction. In order to achieve this objective, we are always at your doorstep and ready to serve you whenever you need us. We look forward to hear from you always.

## Service & Support

**SRICO is committed to deliver the best Customer support across India through SRICO Service Centres:**

### **Product Selection, Application support, Consultancy & Technical Support:**

With our experienced technical experts, We support our customers in choosing the right product & accessories, solutions based on application. Our team provides Technical consultancy and support to customer for an optimised solution.

### **After Sales Service and Technical Support**

Consignment verification, Installation/commissioning, Product demonstration, Training, General maintenance, and safety precautions are explained, documented, and given to customer during the implementation of the project.

### **Service Partner: JULABO**

We provide Service and technical support throughout India, we will inspect/troubleshoot and Service all JULABO Products. Despite the age or condition, we make every effort to ensure that your product is serviced and operational, with better performance. JULABO products are widely known to perform, with a low cost of ownership, for many years after first installation. Its not rare to see JULABO products fully operational, even in the harshest of applications, for 20+ years. We have optimized local inventory levels on service components and spare parts for many of our products.

We provide service not only for SRICO sold products but also for those products which was supplied by our OEM suppliers.

## **Preventive Maintenance: Annual Maintenance Contract/ Comprehensive Maintenance Contracts:**

The products represented by SRICO are of high quality and reliability. We understand that our customers especially from **production processes** rely on us to provide durable product performance 24x7. SRICO offers fully customizable and standard Preventive maintenance packages that helps to ensure your instruments are looked after and maintained so that they will live up to your expectations.

We believe "**Prevention is better than cure**". Keeping the instruments Clean, monitored, maintained regularly can help in having service free equipment which keeps the downtime to minimum and service expenses to the lowest. More over it will be worry free for the customer. We encourage you to take up Maintenance contracts.

### **IQ/OQ Documentation:**

We provide IQ/OQ documentation and implementation services to our Pharma Industries. We have complete infrastructure and necessary tools and equipments which are calibrated by Accredited laboratory to implement 100% to fulfill any international standards.

Our Service department is ready and eager to provide support whenever it is required. You can expect prompt and competent service support for any concerns you may have, whether related to operations or service.

***For Service support on the product, please e-mail at [service@srico-labworld.com](mailto:service@srico-labworld.com) with details such as the Brand Name, Model Name, Serial Number, Barcode Number with a brief description such as error message etc which helps us to provide the quick solution.***

## **We serve mainly the customers in the application field of Quality Control, R&D, and Production**

- Pharmaceutical Industries
- Chemistry, Chemical and Petrochemical Industries
- Automotive, E-mobility, Electronics & semiconductor Industries
- Testing Laboratories
- Life Sciences and Biotechnology
- Agricultural Sciences
- Food and Beverages
- Environmental Sciences
- Universities, Institutions, Government Organizations in the above field.

Model	Order No.	Features/ Main Specs.	Working Temp. Range (°C)	Cooling capacity (KW) at		
				+20	0	-20 °C

CORIO Refrigerated/Heating Circulators

HSN Code:84198998



<b>CD-200F</b>	9012701.N1	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Temperature Stability :±0.03°C</li> </ul>	-20 ..... 150	0.22	0.17	0.06
<b>CD-310F</b>	9012713.N1	<ul style="list-style-type: none"> <li>• Pump flow rate:15 lpm</li> </ul>	-30 ..... 150	0.31	0.28	0.13
<b>CD-450F</b>	9012714.N1	<ul style="list-style-type: none"> <li>• Pump Pressure:0.35 bar</li> <li>• USB interface</li> </ul>	-30 ..... 150	0.45	0.38	0.17
<b>CD-800F</b>	9012715.N1	<ul style="list-style-type: none"> <li>• Uses natural refrigerants</li> </ul>	-40 ..... 150	0.85	0.75	0.4



<b>CP-200F</b>	9013701.N1	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> </ul>	-20 ..... 200	0.2	0.15	0.02
<b>CP-310F</b>	9013713.N1	<ul style="list-style-type: none"> <li>• Temperature Stability :±0.03°C</li> </ul>	-30 ... +200	0.3	0.27	0.12
<b>CP-450F</b>	9013 714.N1	<ul style="list-style-type: none"> <li>• Pump flow rate:8.....27 lpm</li> <li>• Pump Pressure:0.1.....0.7 bar</li> </ul>	-30 ... +200	0.44	0.37	0.16
<b>CP-800F</b>	9013715.N1	<ul style="list-style-type: none"> <li>• USB and RS232 interface</li> </ul>	-40 ... +200	0.84	0.74	0.39
<b>CP-1200F</b>	9013717.N1	<ul style="list-style-type: none"> <li>• Uses natural refrigerants</li> </ul>	-50 ..... +200	1.24	1.09	0.62

Model	Order No.	Features/ Main Specs.	Working Temp. Range (°C)	Cooling capacity (KW) at		
				+20	0	-20 °C

DYNEO Refrigerated/Heating Circulators

HSN Code:84198998



<b>DD-310F</b>	9021713.N1	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Temperature Stability :±0.01°C</li> </ul>	-30 ... +200	0.3	0.27	0.12
<b>DD-450F</b>	9021714.N1	<ul style="list-style-type: none"> <li>• Pump flow rate:8.....27 lpm</li> <li>• Pump Pressure:0.1.....0.7 bar</li> </ul>	-30 ... +200	0.44	0.37	0.16
<b>DD-800F</b>	9021715.N1	<ul style="list-style-type: none"> <li>• External Pt100 Sensor connection</li> <li>• USB and RS232 interface or analog interface (optional)</li> </ul>	-40 ... +200	0.84	0.74	0.39
<b>DD-1200F</b>	9021717.N1	<ul style="list-style-type: none"> <li>• Uses natural refrigerants</li> </ul>	-50 ... +200	1.24	1.09	0.62

Model	Order No.	Features/ Main Specs.	Working Temp. Range (°C)	Cooling capacity (KW) at		
				+20	0	-20 °C

MAGIO Refrigerated/Heating Circulators

HSN Code:84198998



<b>MS-450F</b>	9032714.N1	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Pump flow rate:16.....31 lpm</li> </ul>	-30 ... +200	0.46	0.39	0.12
<b>MS-800F</b>	9032715.N1	<ul style="list-style-type: none"> <li>• Pump Pressure:0.24.....0.92 bar</li> <li>• External Pt100 Sensor connection</li> <li>• USB, ethernet and RS232 interface</li> </ul>	-40 ... +200	0.86	0.76	0.41
<b>MS-1200F</b>	9032717.N1	<ul style="list-style-type: none"> <li>• Uses natural refrigerants</li> <li>• Temperature Stability:±0.01°C</li> </ul>	-50 ... +200	1.26	1.11	0.64

Model		Order No.	Features/ Main Specs.	Working Temp. Range (°C)	Filling volume (L)		
CORIO Heating Circulators with Open Baths				HSN Code:84198998			
	<b>CD-B5</b>	9012405	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Temperature Stability :±0.03°C</li> <li>• Pump flow rate:15 lpm</li> <li>• Pump Pressure:0.35 bar</li> <li>• USB interface</li> </ul>	50.....+150	3.5 ... 5		
	CD-B19	9012419		50.....+150	14....19		
CORIO Heating Circulators				HSN Code:84198998			
	<b>CP-BC6</b>	9013506	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Temperature Stability :±0.02°C</li> <li>• Pump flow rate:8.....27 lpm</li> <li>• Pump Pressure:0.1.....0.7 bar</li> <li>• USB interface</li> <li>• RS232 interface</li> </ul>	50.....+200	4.5.....6		
DYNEO Heating Circulators				HSN Code:84198998			
	DD-BC6	9021506	<ul style="list-style-type: none"> <li>• Heating Capacity :2kW</li> <li>• Temperature Stability :±0.01°C</li> <li>• Pump flow rate:8.....27 lpm</li> <li>• Pump Pressure:0.1.....0.7 bar</li> <li>• USB interface</li> <li>• RS232 interface or analog interface(optional)</li> <li>• External Pt100 Sensor Connection</li> </ul>	50.....+200	4.5.....6		
MAGIO Heating Circulators				HSN Code:84198998			
	<b>MX-BC6</b>	9033506	<ul style="list-style-type: none"> <li>• Heating Capacity :3kW</li> <li>• Temperature Stability :±0.01°C</li> <li>• Pump flow rate: 16.....31 lpm</li> <li>• Pump Pressure:0.24.....0.92 bar</li> <li>• USB, Ethernet and RS232 interface</li> </ul>	50..... +250	4.5.....6		
Model		Order No.	Features/ Main Specs.	Filling Volume (L)	Cooling capacity (KW) at +20 0 -20 °C		
JULABO Recirculating Coolers/Chillers, FL-Series				HSN Code:84198998			
	FL 300	9660003	<ul style="list-style-type: none"> <li>• Temperature range :-20 to 40°C</li> <li>• Filling level indicator</li> <li>• Temperature Stability :±0.5 °C</li> <li>• Pump flow rate( max): 23 lpm</li> <li>• Pump Pressure( max): 1 bar</li> <li>• RS232 interface</li> </ul>	3.....4.5	0.3	0.2	0.1
	<b>FL 601</b>	9661006		5.5.....8	0.6	0.4	0.2
	FL 1701	9661017		12.....17	1.7	1.1	0.4

Model	Order No.	Features/ Main Specs.	Pump flow rate flow pr ( lpm / bar)	Cooling capacity (KW) at +20 +10 0°C		
-------	-----------	-----------------------	--	---	--	--

JULABO Recirculating Coolers/Chillers, F-Series

HSN Code:84198998



<b>F250</b>	9620025	<ul style="list-style-type: none"> <li>Temperature range : 0 to 40°C ( Except F250)</li> <li>Temperature Stability : ±0.5°C</li> <li>Filling level indicator</li> <li>Easy filling and draining</li> <li>Suitable fluids : water, water-glycol mixture</li> </ul>	15/0.35	0.25	0.22	0.18
F500	9620050		24/0.5	0.5	0.4	0.25
<b>F1000</b>	9620100		23/1.0	1.0	0.7	0.35

Model	Order No.	Features/ Main Specs.	Bath opening (W X L / D) (cm)	Filling Volume (L)
-------	-----------	-----------------------	----------------------------------	-----------------------

PURA Water Baths

HSN Code : 84198998



<b>PURA 14</b>	9550514	<ul style="list-style-type: none"> <li>Temperature range : RT...+99.9°C</li> <li>Temperature Stability : ±0.15°C</li> <li>Heating capacity: 2kW</li> <li>Built in dry running protection</li> <li>Integrated timer</li> </ul>	33 x 27 / 14	2 ... 14
<b>PURA 22</b>	9550522		55 x 27 / 18	3.4 ... 25.5

Model	Order No.	Features/ Main Specs.	Internal Circulation / Temperature stability (°C)
-------	-----------	-----------------------	--

JULABO Shaking Water Baths

HSN Code : 84198998



<b>SW22</b>	9550322	<ul style="list-style-type: none"> <li>Temperature range : RT.....+99.9 °C</li> <li>Shaking (Accuracy): ±15 rpm</li> <li>Shaking frequency(adjustable):20.....200 rpm</li> <li>Shaking stroke 15 mm</li> <li>Filling volume:8.....20 L</li> <li>Warning and cut-off protection for high/low temperature</li> </ul>	No / ±0.2
SW23	9550323		Yes / ±0.02




Model	Order No.	Features/ Main Specs.	Cooling capacity (KW) at +20 -40 -80°C		
-------	-----------	-----------------------	---	--	--



JULABO Immersion Cooler

HSN Code : 84198998






<b>FT 903</b>	9650893	<ul style="list-style-type: none"> <li>Temperature range : -90.....30°C</li> <li>Integrated temperature control and display as well as external Pt100 sensor</li> <li>Dry ice substitution</li> <li>Commonly used for -78°C organic synthesis reactions for R&amp;D purpose</li> </ul>	0.3	0.23	0.05
FT 402	9650842	<ul style="list-style-type: none"> <li>Temperature range : -40.....30°C</li> <li>Integrated temperature control and display as well as external Pt100 sensor</li> <li>Dry ice substitution</li> <li>Rapid cooling of liquids down to low temperatures</li> </ul>	Cooling capacity (KW) at +20 0 -40°C		
			0.45	0.3	0.03

Model	Order No.	Features/ Main Specs.
Berghof High Pressure reaction vessel for digestion and synthesis( DAB Series)		HSN Code:84198998
 <b>DAB - 2</b>	5215090	<ul style="list-style-type: none"> <li>Material: Stainless steel 316Ti (1.4571) combined with TFM-PTFE</li> <li>Max. temperature:250°C</li> <li>Max. pressure:200 bar</li> <li>Volume: 25 / 50 ml( with PTFE lining)</li> <li>Standard fittings: Rupture Disc</li> <li>Can be integrated with heating block</li> </ul>
Berghof High Pressure reaction vessel for digestion and synthesis( DB Series)		HSN Code:84198998
 <b>DB-300</b>	10005516	<ul style="list-style-type: none"> <li>Material: Stainless steel 316Ti (1.4571) combined with TFM-PTFE</li> <li>Max. temperature:230°C</li> <li>Max. pressure:200 bar</li> <li>Volume: 310 ml( with PTFE lining)</li> <li>Standard fittings: Rupture Disc, Dip Tube, Valve/Tool, Pressure Sensor</li> <li>Can be integrated with hot plate/heating jacket or double jacket fluid systems</li> </ul>
Berghof High Pressure Reaction (BR Series)		HSN Code:84198998
 <b>BR-100</b>	10000178	<ul style="list-style-type: none"> <li>Material: Stainless Steel 316Ti (1.4571) or Hastelloy C-22 (2.4602)</li> <li>Max. temperature: 300° C( 230° C with PTFE insert)</li> <li>Max. pressure: 200 bar</li> <li>Volume: approx. 170 ml( with PTFE lining)</li> <li>Standard fittings: Rupture Disc, Dip Tube, Valve</li> <li>Can be integrated with hot plate/heating jacket</li> <li>Pressure measurement : Analog or digital</li> </ul>

Model	Order No.	Features/ Main Specs.	Volume (L)	Drain
Elmasonic Easy - Ultrasonic Bath			HSN Code : 84798997	
	<b>Easy 60H</b>	1118894	5.9	Yes
	<b>Easy 100H</b>	1118896	9.5	Yes
		<b>(Bath lid included in supply schedule)</b>		
Elmasonic Select - Ultrasonic Bath			HSN Code : 84798997	
	<b>Select 60</b>	1106990	5.9	Yes
	<b>Select 100</b>	1106991	9.5	Yes
	<b>Select 900 (Industrial Model)</b>	1108778	89	Yes
		<b>(Bath lid included in supply schedule)</b>		




Model	Order No.	Features/ Main Specs.	Ultim.vac (mbar)	Max. pumping speed (m <sup>3</sup> /h)	
VACUUBRAND Chemistry diaphragm pumps			HSN Code : 8414		
	<b>MZ 2C NT</b>	20732302	7	2	
	MD 4C NT	20736402	1.5	3.4	
	MZ 2C NT AK+ EK	20732602	7	2	
	MD 1C AK+ EK	20696622	2	1.3	
	MD 4C NT AK+ EK	20736702	1.5	3.4	
	<b>MZ 2C NT AK Synchro EK</b>	20732802	• Long diaphragm life, maintenance free drive system	7	2
	<b>MD 4C NT AK Synchro EK</b>	20736802	• Oil free vacuum pumps	1.5	3.4
	<b>PC 610 Select</b>	20737157	• Vario Select Model Comes with digital Controller	1.5	3.4

Model	Order No.	Features/ Main Specs.	Speed Range (RPM)	Max Volume (L)	
Inductive 2mag Single Point Stirrers			HSN Code : 84798200		
	<b>MIX 1</b>	30001ON	• Maintenance and free continuous Operation	100 - 2,000	10
	<b>MIX 1 XL</b>	30201	• Ultra flat, wear free magnetic stirrer with 1 stirring position	70 - 2,000	40
Inductive 2mag Multiple Stirrers			HSN Code : 84798200		
	<b>MIX 6</b>	30006ON	<ul style="list-style-type: none"> <li>Ultra-flat magnetic stirrer with multi stirring positions</li> <li>Maintenance- and wear-free</li> <li>For different vessel sizes</li> <li>Outstanding long-life quality</li> </ul>	100 - 2,000	3
	MIX 15	30015ON		100 - 2,000	3
	<b>MIX 15 eco</b>	30115ON		120 - 1,200	1.5
	<b>MIX 4 MS</b>	30404ON		100 - 2,000	3

Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------

WIGGENS Rotary Evaporator



HSN Code : 84198990

	<p><b>STRIKE 185</b></p>	<p>SQED148417</p>	<ul style="list-style-type: none"> <li>• Vapor rising type model</li> <li>• Bath Capacity: 5Litres</li> <li>• Bath Temperature : 180°C</li> <li>• Rotation speed: 20 to 300 rpm</li> <li>• Cooling Surface area: 1500 cm<sup>2</sup></li> <li>• Evaporating and receiving flask up to 2 litres</li> <li>• 4.3" monochromatic LCD touch screen</li> </ul>
---	--------------------------	-------------------	--

Model	Order No.	Features/ Main Specs.	Top Plate Dimensions (mm)
-------	-----------	-----------------------	---------------------------

WIGGENS Digital Hotplate Stirrer


HSN Code : 84798200

	<p>WH260-H</p>	<p>W3012603.01</p>	<ul style="list-style-type: none"> <li>• Max. Set Temperature (top plate): 450°C</li> <li>• Stirring speed: 100 to 1500 rpm</li> <li>• Heating capacity: 800 W</li> <li>• LCD Digital display/ knob control</li> <li>• Ceramic glass top plate</li> <li>• Pt 100 sensor for temperature control</li> <li>• USB interface</li> </ul>	<p>180 x 180</p>
	<p><b>WH260-R</b></p>	<p>W3012605.01</p>	<p><b>( Package includes Pt 100 Sensor + Holder + Octahedral Stir bar )</b></p>	<p>Φ135</p>

Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------

WIGGENS Soft Dry Bath


HSN Code : 84798200

	<p><b>SDB + WH260-R</b></p>	<p>SDB - 1+ SDB - 2+ W3012605.01</p>	<ul style="list-style-type: none"> <li>• Temperature range: ( RT+5) to 150°C</li> <li>• Suitable for volumes up to 1000 ml</li> <li>• Can be mounted on top of 135 mm round hotplate top</li> <li>• Uniform heat transfer and fast heat conduction</li> <li>• SDB-1: Dry bath tank and jacket</li> <li>• SDB-2: Alloy seeds, 2 kg</li> </ul>
---	-----------------------------	--	--


Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------


WIGGENS Hotplate Stirrer


HSN Code : 84798200

	<p><b>WH380</b></p>	<p>W3013803.01</p>	<ul style="list-style-type: none"> <li>• Max. set temperature: 550° C</li> <li>• Stirring speed : 100 to 1500 rpm</li> <li>• Capacity: 30 L (H<sub>2</sub>O)</li> <li>• Heating capacity: 1.2kW</li> <li>• Top plate area ( W× L): 280 × 280 mm</li> <li>• Ceramic glass top plate</li> <li>• LCD display</li> </ul> <p><b>( Package includes Pt 100 Sensor + Holder +Stir bar )</b></p>
---	---------------------	--------------------	--

Model	Order No.	Features/ Main Specs.	Display / Control	
WIGGENS Overhead Stirrer			HSN Code : 84798200	
	<b>WB2000-M</b>	100300-P2	<ul style="list-style-type: none"> <li>• Speed range: 40-2000 rpm</li> <li>• Max. Capacity: 50 L(H<sub>2</sub>O)</li> <li>• Maximum viscosity: 20000 cps</li> <li>• RS232 interface( WB2000-C)</li> <li>• Internal overload protection</li> </ul>	LED Display / Knob Control
	<b>WB2000-C</b>	100500-P2	<ul style="list-style-type: none"> <li>• Internal overload protection</li> </ul> <p><b>(Package includes stand and SS Impeller )</b></p>	LCD Display / On - Touch Control
Model	Order No.	Features/ Main Specs.		
WIGGENS Ultrasonic Shaking Water Bath			HSN Code : 84798200	
	<b>WUS22</b>	W30380122	<ul style="list-style-type: none"> <li>• Combines the function of ultrasonic cleaner and shaking water bath</li> <li>• Shaking stroke: 20/30/40 mm</li> <li>• Temperature range: 20 to 80°C</li> <li>• Volume: 20 L</li> <li>• Heating power: 550 W</li> <li>• Rack is easy to remove</li> </ul>	
Model	Order No.	Features/ Main Specs.	Display/Control	
WIGGENS Vortex Shaker			HSN Code : 84798200	
	<b>Vortex 3000 Elite</b>	W3060215	<ul style="list-style-type: none"> <li>• Highly Touch Sensitive</li> <li>• Suitable to work in fume hoods and on sterile workbenches</li> <li>• Rubber feet guarantee stability of the shaker</li> <li>• Power cutoff function in case of electrical overload</li> <li>• Speed Range : 100 - 3000 rpm</li> </ul>	LED Display / Knob Control
Model	Order No.	Features/ Main Specs.	Platform (WxD)mm	
WIGGENS Orbital Shaker			HSN Code : 84798200	
	<b>WS-50DR</b>	3A226C	<ul style="list-style-type: none"> <li>• Motion type: Reciprocal</li> <li>• Load capacity of up to 12 kg</li> <li>• Speed Range: 10.....250 rpm</li> <li>• Shaking motion can be set in up to 6 different ways</li> <li>• Timer function for maximum stability</li> </ul>	320 x 260
Model	Order No.	Features/ Main Specs.		
WIGGENS Parallel Reaction Station			HSN Code : 84798200	
	<b>PRS-6</b>	PR202110-100	<ul style="list-style-type: none"> <li>• Temp range : RT+5 to 180°C</li> <li>• Stirring speed : 0 to 600 rpm</li> <li>• Vacuum : 20 mbar</li> <li>• Max. load 6 reaction vessels with flask capacities 50ml, 100ml &amp; 250ml.</li> </ul>	

Model	Order No.	Features/ Main Specs.	Capacity (ml)
Dewar flasks - cylindrical			HSN Code : 70172000
	<b>9 C</b>	10211	1000
	<b>12 C</b>	10214	1500
	<b>13 C</b>	10215	2000
	<b>G 9 C</b>	1068	1000
	<b>G 18 C</b>	10614	2500
		<ul style="list-style-type: none"> <li>Reliable and economical</li> <li>Dewar flasks according to DIN 12492</li> <li>Glass material according to ISO 3585</li> <li>Nominal capacity from 100ml to 8 Litres</li> <li>Protective casing of blue-coated metal</li> <li>Models with side grip available</li> </ul>	

Model	Order No.	Features/ Main Specs.	Volume (ml)	Accuracy (± ml)
WITEG Bottle-Top Digital Burette TITREX			HSN Code : 90318080	
	<b>TITREX Fine adjustment</b>	5 497 150	0 - 50	0.03
		<ul style="list-style-type: none"> <li>Exclusive instrument with 0 % loss of reagent</li> <li>360° rotatable valve</li> <li>Used as dispenser for up to 50 ml</li> <li>Used as burette for up to 99.99 ml</li> <li>RS232 interface</li> <li>Two in one instrument: dosing &amp; titration</li> </ul>		

Model	Order No.	Features/ Main Specs.	Volume (µl)	Accuracy (±µl)
WITEG Bottle-Top Dispenser - Minispensor			HSN Code : 90318080	
	<b>Minispensor (Yellow)</b>	5 371 101	50+100	1.5
	<b>Minispensor (Red)</b>	5 371 525	250+500	5
	<b>Minispensor (Blue)</b>	5 371 950	500+1000	6
	<b>Minispensor (Green)</b>	5 371 990	1000+2000	12
		<ul style="list-style-type: none"> <li>Ideal for fixed micro volume</li> <li>Used for crystalline, alkaline and organic solutions</li> <li>Each model is able to dispense two definite volumes</li> <li>Four color-coded models available</li> <li>Easy to clean, autoclavable at 121°C</li> </ul>		

Model	Order No.	Features/ Main Specs.
DAIHAN Digital Hotplate Stirrer		HSN Code : 84798240



**MSH500**

DH.WMH00500.S

- Max. speed range: 80....1500 rpm
- Max. stirring capacity: 20L (H<sub>2</sub>O)
- Max Temp 500°C
- Solid Ceramic Glassplate : 200 x 200 mm
- LCD display
- Accurate Temp. Control of the Sample in the Vessel using Pt100 Sensor

**( Package includes Stirring bar, PT100 temp probe, support rod, clamp)**

Model	Order No.	Features/ Main Specs.	Display
DAIHAN Hotplate Stirrer		HSN Code : 84798240	



MSH-20A

DH.WMH03120

- Max. speed range : 80....1500 rpm
- Max. stirring capacity: 20L (H<sub>2</sub>O)
- Max Temperature: 380°C
- Plate size: 180 x 180 mm
- Ceramic coated Plate

Analog

**MSH-20D**

DH.WMH03021.S

**( MSH-20D Package includes Stirring bar, PT100 temp probe, support rod, clamp)**

Digital

Model	Order No.	Features/ Main Specs.	Stirring position
DAIHAN Multi-Hotplate Stirrer		HSN Code : 84798240	



**SMHS-6**

DH.WMH03506

- Max. speed range : 80...1500 rpm
- Max. stirring capacity is 20L (H<sub>2</sub>O)
- Max temp range: 350 °C
- Ceramic coated plate : 140 x 140 mm
- Independent Heating and Stirring Control
- LCD display

6

Model	Order No.	Features/ Main Specs.	Display
DAIHAN Magnetic Stirrer		HSN Code : 84798240	



**MS-20A**

DH.WMS03122

- Max. speed range: 80.... 1500 rpm
  - Max. stirring capacity: 20L (H<sub>2</sub>O)
  - Ceramic coated Plate 180 x 180 mm
  - Smart Design of Body made by powder Aluminum Die Casting
- (Package includes Stirring bar)**

Analog

Model	Order No.	Features/ Main Specs.	Heat up time to 150 °C (min)	Capacity (L)
DAIHAN Forced Air Oven		HSN Code : 85142010		



**OF-W105**

DH.WOF07105

- Temp range:(RT+5).....250°C
- Temp sensor: Pt100 sensor
- LCD display , Timer & Alarm
- RS232 Interface
- Window Model

45

105

OF-W155


DH.WOF07155

**( Package includes 2 stainless steel wire shelf)**


40

155


Model	Order No.	Features/ Main Specs.	Heat up time to 150 °C (min)	Capacity (L)
DAIHAN Vacuum Oven			HSN Code : 85142010	

	OV - 20	DH.WOV03020	<ul style="list-style-type: none"> <li>Vacuum Range :10 -750 mmHg</li> <li>Temp range:(RT+10°C).....200°C</li> <li>Temp sensor: Pt100 sensor</li> <li>LCD display , Timer &amp; Alarm</li> <li>RS232 Interface</li> </ul>	90	20
	<b>OV - 70</b>	DH.WOV03070		<b>( Package includes 2 Shelves)</b>	100


Model	Order No.	Features/ Main Specs.	Heat up time to 150 °C (min)	Capacity (L)
DAIHAN Smart Vacuum Oven			HSN Code : 85142010	

	<b>SOV - 30</b>	DH.SWOV03030	<ul style="list-style-type: none"> <li>Vacuum Range :10 -750 mm Hg</li> <li>Temp range:(RT+10°C).....200°C</li> <li>Temp sensor: Pt100 sensor</li> <li>4 inch Full touch screen</li> <li>Smart-lab controller</li> <li>Timer and alarm function</li> </ul>	100	30
	SOV - 70	DH.SWOV03070		<b>(Package includes 2 Shelves)</b>	100

Model	Order No.	Features/ Main Specs.	Capacity (L)	Temp(°C)
DAIHAN Programmable Digital Muffle Furnace			HSN Code : 85142010	

	<b>FX-03</b>	DH.WF21.03	<ul style="list-style-type: none"> <li>4-Side Heating</li> <li>Safety: over temp, sensor error detection</li> <li>Timer &amp; Alarm</li> <li>LCD display</li> <li>Digital PID Controller</li> <li>Temp sensor: K type thermocouple</li> </ul>	3	1000
	FHX-05	DH.WFH22.05		<b>( Package includes ceramic fiber plate)</b>	4.5

Model	Order No.	Features/ Main Specs.	Basket Dimensions (D X H) mm	Capacity (L)
DAIHAN Digital Autoclave			HSN Code : 84192000	

	<b>MaXterile 100R</b>	DH.WACR2100P	<ul style="list-style-type: none"> <li>Temp range:(RT + 5°C).... 132°C</li> <li>Pressure: 2 Kgf/cm<sup>2</sup></li> <li>Water Low Level Detection</li> <li>LCD display</li> <li>With PED (Pressure Equipment Directive) certification ,Φ 3.0 mm thickness tank</li> <li>Safety: Over temp, Pressure, current protection, sensor error detection.</li> </ul>	420 x 240	100
				<b>( Package includes two stainless steel wire basket )</b>	

Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------

DAIHAN Multifunction Vortex Mixer

HSN Code : 84798210



**MaXshake VM30**

DH.WVM00031

- Speed range: 0 ...3300 rpm
- Shaking Motion: Orbital
- Max Load: 500 g
- Electronic speed control for constant speed even during changes in load
- Universal head for a variety of mixing applications
- Micro tube platform head also available

**(Package includes platform head, Pop -off cup head, remover applicator)**

Model	Order No.	Features/ Main Specs.	Shaking motion
-------	-----------	-----------------------	----------------

DAIHAN Shaker

HSN Code : 84798240



**SHK 2.0**

DH.WSO00300

- Speed range: 10 ...300 rpm
- Max. load: 10 Kg
- Amplitude of rotation: 10mm
- Shaking platform size: 255 x 255 mm
- LCD display
- Alarm: Error status and Timer end.
- Programmable
- Continuous Shaking upto 99hr.59min

Orbital

**SHK 2.R**

DH.WSR00300

Reciprocal

Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------

DAIHAN Heating Dry Bath Incubator

HSN Code : 84198990



**HB-48**

DH.WHB02000

- Temp range: (RT+5)...150°C
- Heating Speed: 5°C / min
- Temp Sensor: Pt100
- Digital LCD display
- Digital timer with alarm for error status and timer-end

**(Package includes block for (48 holes for 1.5/2 ml ) & removal tool)**

Model	Order No.	Features/ Main Specs.
-------	-----------	-----------------------

DAIHAN Digital Homogenizers

HSN Code : 8479.82-3000





**HG-15D (Set A)**



DH.WHG02019

**HG-15D (Set B)**




DH.WHG02020


- Speed Range (rpm) : 2000-27000 (without Load)
- High efficiency dispersing tool made of SS and PTFE
- Designed for liquid and tissue samples
- LCD for Speed and Power bar graph
- Set A includes Dispersing tool with rotor  $\phi$  of 12.8 mm for up to 1000ml of sample volumes
- Set B includes Dispersing tool with rotor  $\phi$  of 20 mm for up to 2500ml of sample volumes

Model	Order No.	Features/ Main Specs.
CAT Overhead Stirrer		HSN Code : 84798200
	<b>R 50</b> 60215-0000	<ul style="list-style-type: none"> <li>• Quick-release chuck</li> <li>• Overload &amp; overheat protection</li> <li>• Continuously adjustable speed</li> <li>• Speed Range:50-1600 rpm</li> <li>• Stirring quantity max. (H<sub>2</sub>O) : 100 L</li> <li>• Viscosity max. : 30,000 mPas</li> </ul> <p><b>(Package includes overhead stirrer with support rods)</b></p>
CAT Homogenizer		HSN Code : 84798200
	<b>X 1000D</b> 60406-0050	<ul style="list-style-type: none"> <li>• Speed range : 4000 to 33,000 rpm</li> <li>• Volume max (H<sub>2</sub>O) : 2 L</li> <li>• DC motor type</li> <li>• Shaft rotation : Counter clockwise</li> <li>• Digital model with rpm display</li> <li>• CE certified</li> </ul> <p><b>(Other accessories to be selected as per application)</b></p>

Model	Order No.	Features/ Main Specs.
EDMUND BUEHLER Universal Shaker		HSN Code : 84798200
	<b>KL-2</b> 6115 000	<ul style="list-style-type: none"> <li>• Ideally suited for 2kg load</li> <li>• Switching from orbital to reciprocating possibility</li> <li>• Run time: 0-120 min/continuous</li> <li>• Stroke length : 8mm</li> <li>• Shaking platform dimensions: 300 x 300 mm</li> <li>• Shaking speed: 30 - 420 rpm</li> </ul> <p><b>(Package includes shaking platform and rubber mat)</b></p>
	<b>SM 30 C</b> 6105 000	<ul style="list-style-type: none"> <li>• Ideally suited for high loads upto 30 Kg</li> <li>• Basic device comes with shaking platform and rubber mat, without rack system</li> <li>• Can be switched from orbital to reciprocating motion</li> <li>• Run time : 0 - 120 min/continuous</li> <li>• Stroke length: 26 mm</li> <li>• Shaking Platform Dimension : 560 x 400 mm</li> <li>• Shaking Speed : 15-300 rpm</li> </ul>



Model	Features/ Main Specs.	Temp Range (°C)	Capacity (L)
METHER -86°C ULT Freezers		HSN Code : 84181020	
	MDF-86V338	-40 to -86°C	338
	<b>MDF-86V408</b>	-40 to -86°C	408
	MDF-86V728	-40 to -86°C	728
<ul style="list-style-type: none"> <li>• Two-compressor cascade refrigeration system</li> <li>• HC refrigeration system, energy saving 50%</li> <li>• Standard USB port, easy to download data</li> <li>• Build-in back-up battery</li> <li>• Casters with stopper for easy moving and fixation</li> </ul>			
METHER -25°C Medical Freezers		HSN Code : 84184080	
	MDF-25V100	-10 to -25 °C	100
	MDF-25V278W	-10 to -25 °C	278
<ul style="list-style-type: none"> <li>• Single or double door deep freezers</li> <li>• LED/LCD digital display</li> <li>• Microprocessor controller</li> <li>• Multiple malfunction alarms</li> <li>• Door lock for storage safety</li> </ul>			
METHER Pharmacy Refrigerators		HSN Code : 84185090	
	MPC-5V226	2-8°C	226
	MPC-5V656	2-8°C	656
<ul style="list-style-type: none"> <li>• Microprocessor control</li> <li>• Optimized space utilization design and adjustable shelf height</li> <li>• Standard with USB port, easy to download data</li> <li>• Build-in back-up battery to display temperature</li> </ul>			

Model	Features/ Main Specs.	Production in 24h (Kg)	Storage capacity (Kg)
BREMA Ice Flaker machine		HSN Code : 84186900	
	<b>GB 903 HC</b>	113	30
	<b>GB 1555 HC</b>	153	55
	<b>G 280 HC + BIN 200</b>	280	200
<ul style="list-style-type: none"> <li>• Granular ice - 80-82% dry</li> <li>• Unit comes with inbuilt storage bin</li> <li>• AISI 304 SS Scotch Brite finish</li> <li>• Ambient temp from +10° C to +43°C</li> <li>• Removable and cleanable air Filter</li> <li>• Automatic water charge</li> </ul>			



# Ultrasonic Cleaning Device



Cleaning Basket




Mute Box



Holders



Inserts



Cleaning Module



Cooling Coil



Pins

- Multi Frequency Unit : 37kHz & 80kHz
- Temp Range: RT to 80°C
- Volume Range : 3L to 90L

# Julabo

THE TEMPERATURE CONTROL COMPANY

# Superior TEMPERATURE TECHNOLOGY for a better **Life**



If undelivered please return to below address

Book Post



## Scientific Research Instruments Company Private Limited

# 42-43, 2nd & 3rd Floor, 1st Cross, Gubbalala, Bengaluru - 560 061

Telephone : 080 4757 2577 | 080 4302 5791

### Sales

info@srico-labworld.com

Mobile : +91 9900674407

### Service

service@srico-labworld.com

Mobile : +91 9900055879

**Bhubaneswar | Hyderabad | New Delhi | Navi Mumbai | Vadodara**

Ahmedabad | Chandigarh | Chennai | Goa | Guwahati | Kolkata | Lucknow | Pune | Thiruvananthapuram | Visakhapatnam

[www.srico-labworld.com](http://www.srico-labworld.com)

SRICO.03/102024